




Peanut WACO SRE

By WALT MOONEY. Our author seasoned this month's article with a discourse on how to choose an airplane to build a model . . . of.

discourse on how to choose an airplane to build a model . . . of.

The final Waco biplane design and corross section aft of the wing. This Waco probably the ultimate in cabin biplane configurations was the graceful Model state. The classic color scheme is also take flight loads. Waco used flying wires on this model. Most of the older models had a multitude of formers and stringers that builded a far multitude of formers and stringers that builded and the fusslegs between the black and there it white pin striping a stringers hat builded and stringers aft of the trim and number color scheme is also take flight loads. Waco used flying wires on this model. Most of the older models had a multitude of formers and stringers that builded out the fusslegs, between the black and there it white pin striping color scheme. Were used but the one to be stored to the stringers were not very appression stringers that builded out the fusslegs between the black and there it. Other builded in the fusslegs between the black and there to. Other builded in the fusslegs to be the stringers were not very appression stringers that builded out the fusslegs to the fussless that the stringers were not very appression stringers that builded out the fussless that the fussless that the stringers were not very appression stringers that a builded out the stringers were not very appression stringers that a builded out the stringers were not very appression stringers that a builded out the stringers were not very appression there is white pin stringers att of the stringers were not very appression stringers were not very appression that the stringers were not very appression to the stringers were not very appression that the stringers were not very appression that the stringers were not very appression to the stri



the fuseling would allow the use of scale tail surfaces, and with the CG as shown on the plann, the model flyse required to get the CG this far forward... Test flights with it farther aft were reratic in pitch, so make sure your model balances as shown.

This model is built in the conventional manner, so no detailed, howto-build-it article is presented here. However, a few points should be mentioned.

Note that the landing gear wire is designed to be on the outside of the leg rather than faired inside the leg. The landing gear leg and its idea and rear struss are cemented rigidly to the fuse landing gear wire but not to the strust. This way the wheel pants are cremented to the landing gear wire but not to the strust. This way the wheels are free to fiex on a hard landing without putting a load noto the fairings. The penalty in looks of the model is very slight and the improvement in model durability is great.

The nose of the model is made to simulate the metal radial cowl. The forward part of the cowl is laminated from three pieces of 3/32 sheet balsa. Aft of these, the cylindrical part of the cowl is made by wrapping 1/16 sheet around Formers 1 and 2. Note that former 2 has a break in it to match the bottom of the winds the six in the bottom of the wing fairs into the voltage in a sort of reverse gulled effect. This thinning of the root rib was figure on the premision to digress a little. One of the questions shall be a real challenge in a so