



HARD Balsa

MIND ON SMALLER WIRE 9 PIERCED

PLUG COVER WITH 1/32 SHEET DOTTED PORTION

FRONT

TYPICAL JOINTS

RUBBER ANCHORAGE

REMOVABLE 1/8 BAMBOO PEG REMOVE PEG-SLIDE RUBBER BEYOND HOLE-SLIP IN PEG

1/8 1/16 HARD

PANELS SPACED 2" EXCEPT WHERE NOTED

TO FIT STAB. SPAR 1/16 DOWELS

NOTE DIRECTION OF WINDING

WASHER CEMENTED TO OUTSIDE OF FUSELAGE TO TAKE WEAR

CEMENT & BIND TO BOTTOM BRACE

1/2 RIBS OF SYMMETRICAL SECTION

1/2 BALSA SHEET 1/32 BOTH SIDES

FOR PACKING REMOVE WIRE FROM TUBE AND FOLD STRUTS BACKWARD

RUDDER ADJUST.

SIZE TO FIT FUSELAGE

BALSA BLOCK

RUDDER ADJUSTMENTS

SOLDER & BIND FRICTION CONTACT

3-1/4 HARD BALSA LAM.

BIND & SOLDER

BIND & CEMENT

F. Baic

